# BRISWIL ENERGY DEVELOPMENT LIMITED



www.briswilenergy.com

## **OUR SERVICES**



#### **IADC EQUIPMENT**

- 2000HP Drilling rig
- 800-1000HP workover rig
- Top drives
- Travelling block
- Crow blocks
- Draw-works
- Rotary table
- Mud pumps
- SCR panels
- Solid control equipment (shale shakers, desilters. Desanders, degaser, screens etc)
- Subsea equipment
- Well control equipment (BOP, Accumulators etc)
- Fishing tools

#### WELL SERVICES EQUIPMENT

- Cementing pump unit
- Stimulation pump unit
- Centrifugal pumps
- Triplex pumps
- Frac pumps
- Batch mixers
- 1502 treating pipes
- 1502 swivels (2-way and 3-way)
- 1502 hammer, FMC and low-torque valves
- 1502 wye
- 1502 Tee
- 13 3/8" cement head with circulating swage
- 9 5/8" cement head with circulating swage

- 7" cement head with circulating swage
- 5-1/5" cement head with circulating swage
- High/low pressure hoses
- Butterfly valves
- High pressure check valves
- Static silos
- Transport silos
- Compressors
- Large volume storage tanks

#### STIMULATION/WELL ACTIVATION EQUIPMENT

- Coiled tubing units
- Nitrogen pump unit
- Acid pump unit (with rubber lining)
- Acid storage tanks
- Stripper rubber
- Pump packings for HT-400, Demay, Serva etc
- Water transport tanks

#### **AGRICULTURAL CHEMICALS**

- Herbicide
- Insecticides
- Fungicides
- Soil fumigants, desiccants, harvest aids and plant growth regulators
- Natural pesticides

#### **CEMENTING CHEMICALS**

- Cement retarders
- Fluid loss agents
- Dispersant

- accelerators
- Gas check additives
- Anti-Gas migration (latex)
- Extenders
- Anti-settlings
- Anti-foaming agent
- Spacer blend
- Chemical wash
- Surfactants
- Flyash
- Cenosphere
- 3 M beads
- Silica flour/sand
- Bentonite
- Barite
- Loss Circulation Material
- Gelling Agent for Spacer
- Mutual Solvent
- Weighing agent for spacer
- Ultrafine cement for squeeze cement

#### STIMULATION CHEMICALS

- POTASIUM CHLORIDE-KCI (clay Stabilizer)
- AMMONIUM CHLORIDE (NH4Cl) Clay stabilizer
- 32% Commercial HCL
- Guargum Based Gel
- Hydrogen Peroxide
- Sodium Hypochlorite
- Mutual Solvents EGMBE (Ethylene Glycol MonoButyl Ether)
- Acetic Acid
- Citric Acid
- DTPA

- Converting Agents (K2CO3)
- KOH
- Oxalic Acid
- Sodium Nitrite
- EDTA
- Benzoic Acid Flakes
- Scale inhibitor (PAA)
- Biocide (Amine or Aldehyde Based)
- Corrosion Inhibitors
- Acid neutralizer
- Non-ionic Surfactant
- Aromatic Solvents
- Non-Emulsifiers
- Acid Foamer
- Rock Salt (graded to Company specification)
- Friction reducers metal to metal
- Friction reducers fluid to metal
- Water Foamer
- Viscoeleastic Surfactant Fluid Divertor
- Glyoxal based H2S Scavenger
- Biodegradable Ball Based Diverter with Ball launcher

#### **DOWNHOLE TOOLS**

- \* Coil tubing internal and external dimple connector for 0.156 wall thickness
- \* Coil tubing connector for 1.75" CT 2-1/8" GRUB screw type Dimple connector
- \* External slip CT connector for 1.75" CT, 2-1/8" OD
- \* Internal Slip type connector for 1.75" CT 1.75" OD
- \* Roll ON type connector for 1.75" CT 2-1/8" OD
- \* MHA 2-1/8" OD with integral spring loaded double flapper check valves, circulation sub (Burst Disc / Ball Drop) and disconnecter. To be provided with required fishing tool
- \* Ball check valve 2-1/8" OD
- \* Back pressure valve (Field adjustable back pressure)- 2-1/8" OD- On callout
- \* Heavy Duty Hydraulic disconnect (Ball drop activated) 2-1/8" OD. To be provided with required fishing tool.

\* Flow Through Knuckle Joint 2-1/8" OD \* Torque through Knuckle Joint 2-1/8" OD \* Shear release joint 2-1/8" (site adjustable) \* Flow activated BOW spring centralizer 2-1/8" OD expandable upto min 7" \* Bow Spring Centralizer – 2-1/8" \* Flow through swivel joint 2-1/8" OD \* Strong Arm Orientation tool (For STD & H2S service) with hydraulic indexing tool- 2-1/8" & 2-7/8"- On callout \* High Impact rotating and jetting nozzle (Heavy Duty – capable to work min 20 hours a day)-\* Multi flow port nozzle (min - 5) downward facing - 2-1/8" OD \* 2-1/8" Full-bore nozzle \* Multi port back flow nozzle (min – 5) upward facing – 2-1/8" OD \* 2-1/8" Flow Activated Hydraulic Knuckle Joint \* 2-1/8" straight bars- 4ft x 3 and 2 ft x 3 \* Venturi Junk Basket - 2-1/8" OD and 2 5/8" with 2 x 6 ft extensions with each set) / VJJB to be compatible with Motors to convert to Rotating VJJB with Burn shoe-Should have different nozzles to work with different pressures \* Venturi Shoes (2-1/16", 2-5/8" & 3-3/8")- On Call out \* 2-1/8" Flow Activated Indexing tools (suitable for 2-7/8", 3-1/2", 4-1/2", 7" & 9-5/8" Tubing Sizes) \* Flow activated Bi-Directional SSD manipulation tools (1-ea of the following sizes) 2.313"; 2.562"; 2.75"; 2.813"; 3.313"; 3.75"; 3.813" SSD Profile \* Flow Activated Hydraulic Tubing end locator (for 2-7/8", 3.5" and 4.5" mule shoe)-On Call out \* Mechanical, scale wax salt and asphaltene removal tools- For 3.5" and 4.5" tubing. \* Ported Crossover from MHA bottom connection to 15/16", 1 11/16", 1.5" SR connection. \* Lead Impression Blocks of different sizes for 2-7/8", 3-1/2", 4-1/2" tubing/casing size. As 1.75", 2", 2.25", 2.4", 2.7", 3", 3.4", 3.7". \* Full-bore nozzle: 2 1/8", 2 3/8", 2 7/8" \* Swage blocks of different sizes for 2-7/8", 3-1/2", 4-1/2" tubing. As 1.75", 2", 2.25", 2.4", 2.7", 3", 3.4", 3.7".

* Gauge Cutter of different sizes for 2-7/8", 3-1/2", 4-1/2" tubing (including but not limited to 1.5", 2", 2.7", 3.5").
* X-Over from 1.5" AMMT to 15/16" SR.
* Flow through fluted centralizer for 2-7/8", 3-1/2", 4-1/2" tubing/casing (including but

### **DRILLING FLUID CHEMICALS**

1.	HT-HP Chemicals and Polymers	Complete range of products
2.	Weighing Agent	<ul><li>Barite</li><li>Haematite</li><li>Calcium Carbonate</li></ul>
3. 4.	Viscosifiers	<ul> <li>Bentonite</li> <li>CMC- LV, HV</li> <li>PAC-LV</li> <li>PAC-RG</li> <li>Xantham Gum (XC Polymer)</li> <li>HEC</li> <li>Resin</li> <li>Synthetic Polymers (PGS (Starch)</li> </ul>
<i>5.</i>	Shale Stabilizer	<ul> <li>Potassium Chloride</li> <li>Sulfonated Asphalt</li> <li>Sulfonated Asphalt- Sodium</li> <li>Sulfonated Asphalt- Potassium</li> <li>Sulfonated Asphalt Supreme</li> <li>Ecostab Forte: An Ecofriendly</li> <li>Substitute for Sulphonated Asphalt</li> </ul>
6.	Deflocculant and Thinners	<ul> <li>Lignite Powder</li> <li>Caustic Lignite</li> <li>Chrome Lignite</li> <li>Potassium Lignite</li> <li>Resinated Lignite</li> <li>Chrome Free Defloc Chrome Free Lignosulphonate</li> </ul>
7. 8.	Fluid Loss Control Additive	<ul> <li>Drilling Starch – Corn / Maize</li> <li>Drilling Starch – Rice</li> <li>Drilling Starch – Tapioca</li> <li>Drilling Starch – HTHP</li> <li>PreGel Starch</li> <li>Resinated Lignite</li> <li>Organophilic Lignite</li> </ul>
	Detergents	<ul><li>Rig Wash</li><li>Drilling Detergent</li></ul>
9.	Lubricants	<ul> <li>Extreme Pressure Lubricant</li> <li>Extreme Pressure Lubricant – Silicate</li> <li>Extreme Pressure Lubricant – Water</li> <li>Extreme Pressure Lubricant – ENV. Friendly</li> <li>Ester Based Lubricant</li> <li>Extreme Pressure Torque Reducer</li> </ul>

	<ul> <li>Spotting Fluid – Weighted</li> </ul>
Spotting Fluids	<ul> <li>Spotting Fluid – Non Weighted</li> </ul>
	<ul> <li>Spotting Fluid – Asphaltic base powder</li> </ul>